




industrial electronics, inc.

Phone (808) 847-4300  
Fax (808) 841-0960

1353 Mookaula Street  
Honolulu, HI 96817



## CABLE SPECIFICATION

Part: 32S14B2

Desc: 14/2 Stranded Shielded H20 Cable CM/CL2/FPL  
Direct Burial (In Conduit) "Sun Res" Waterblock Tape



|                    |   |
|--------------------|---|
| AWG                | 14 Awg 7 Strand Bare Copper   |
| CONDUCTORS:        | 2   |
| INSULATION:        | PVC   |
| Nominal Wall       | .010"   |
| Shield             | Waterblocking Shielded Tape   |
| Color Code         | Blk, Red  |
| % Overlap          | 20  |
| Drain              | NA  |
| Jacket             | PVC / Black   |
| Nominal Wall       | .025"   |
| Nominal OD         | .259"   |
| TEMPERATURE RATING | 75C   |
| OPERATING VOLTAGE  | 300V  |
| CHARACTERISTICS    | Twisted together with a waterblocking shielded tape and jacketed                                    |
| PRINT              | 14 Awg CM or CL2 or FPL 75C C(ETL) US SHLD 2 COND<br>"Direct Burial In Conduit" Sun-Res Made In USA |

Industrial Electronics, Inc. makes no warranties as to the suitability of a product chosen for a particular use.

Specifications subject to change without notice.

Spec issue date: 1-19-17