		ndustrial electronics, inc. Phone (808) 847-4300 Fax (808) 841-0960 1353 Mookaula Street Honolulu, HI 96817 CABLE SPECIFICATION	
Part:	P02S18B6	JTERTS.	
Desc:	18/6 Stranded Shield	6 Stranded Shielded Plenum CMP	
	AWG	18 Awg 7 Strand Bare Copper	
	CONDUCTORS:	6	
	INSULATION:	PVC-Plenum	
	Nominal Wall	.008"	
	SHIELD:	Aluminum Mylar	
	COLOR CODE	Black, Red, Wht, Grn, Org, Yel	
	% OVERLAP	20	
	DRAIN	24 Awg 7 Strand Tinned Copper	
	JACKET	Plenum / White	
	NOMINAL WALL	.013"	
	NOMINAL OD	.205"	
	TEMPERATURE RATING	75C	
	OPERATING VOLTAGE	E 300V	
	CHARACTERISTICS	Twisted, Shielded and Jacketed	
	PRINT	18 AWG CMP or CL2P or FPLP 75C (ETL) US Shid 6 COND. Made In USA	

Industrial Electronics makes no warranties as to the suitability of a product chosen for a particular use.

Specifications subject to change without notice.

Spec issue date: 12-26-14