		industrial electronics, inc. Phone (808) 847-4300 Fax (808) 841-0960 1353 Mookaula Street Honolulu, HI 96817	
CABLE SPECIFICATION			
Part:	P04S16A2	INTERTER.	
Desc:	16/2 Solid Shielded Fire Alarm Cable Plenum FPLP		
		~2/STEO-	
	AWG	16 Awg Solid Bare Copper	
	CONDUCTORS:	2	
	INSULATION:	PVC-Plenum	
	Nominal Wall	.008"	
	SHIELD:	Aluminum Mylar	
	COLOR CODE	Black, Red	
	% OVERLAP	20	
	DRAIN	22 Awg 7 Strand Tinned Copper	
	JACKET	Plenum / Red	
	NOMINAL WALL	.014"	
	NOMINAL OD	.177"	
	TEMPERATURE RATING	-20C to 75C	
	OPERATING VOLTAGI	E 300V	
	CHARACTERISTICS	Twisted, Shielded and Jacketed	
	PRINT	16 AWG CMP or CL2P or FPLP 75C (ETL) US Shid 2 COND. Made In USA	

Industrial Electronics makes no warranties as to the suitability of a product chosen for a particular use.

Specifications subject to change without notice.

Spec issue date: 11-7-14