




industrial electronics, inc.

Phone (808) 847-4300

Fax (808) 841-0960

1353 Mookaula Street
Honolulu, HI 96817



CABLE SPECIFICATION

Part: PMCS18B1-7

Desc: 18/1 PR Shielded Mid-Cap Plenum CMP, All materials used
in the manufacture and test of this product shall comply with
UL Subjects 13, 444, 910 and 1581



AWG	18 Awg 7 Strand (7/26) Tinned Copper
CONDUCTORS:	1 Pair (6 Twists Per Ft) Balck - White
INSULATION:	FEP Foam
Nominal Wall	.012"
SHIELD:	Tape with Aluminum Mylar (Foil Out)
COLOR CODE	Black - White
DRAIN	20 Awg 7 Strand (7/28) Tinned Copper
JACKET	Plenum Rated PVC
NOMINAL WALL	.015"
NOMINAL OD	.178"
TEMPERATURE RATING	75c
OPERATING VOLTAGE	300V
JACKET COLOR	Violet
PRINT	"COMM-TRUNK E102194 CL3P OR CMP 18 AWG 75C. (UL) C(UL) FT-6"

Electrical Data

Capacitance: 23.2 PF/FT, Conductor to Conductor
 Impedence: 58 Ohms
 Velocity of Propagation 75%

Note: Each reel is sequentially marked for footage, 0-1000FT., repeat

Industrial Electronics makes no warranties as to the suitability of a product chosen for a particular use.

Specifications subject to change without notice.

Spec issue date: 10-15-14